



5BK7-A

5BK7-A
TO
5BR8

MEDIUM-MU TWIN TRIODE

9-PIN MINIATURE TYPE

For use in direct-coupled cathode-drive circuits of TV tuners in equipment having series heater-string arrangement

The 5BK7-A is the same as the 6BK7-B except for the following items:

Heater, for Unipotential Cathodes:

Voltage.	4.7	ac or dc volts
Current.	0.6	amp

5BQ7-A

MEDIUM-MU TWIN TRIODE

LOW-NOISE 9-PIN MINIATURE TYPE

For use in direct-coupled cathode-drive circuits of TV tuners in equipment having series heater-string arrangement

The 5BQ7-A is the same as the 6BQ7-A except for the following items:

Heater, for Unipotential Cathodes:

Voltage.	5.6	ac or dc volts
Current.	0.45	amp
Warm-up time (Average)*.	11	sec

5BR8

MEDIUM-MU TRIODE— SHARP-CUTOFF PENTODE

9-PIN MINIATURE TYPE

Intended for use in equipment having series heater-string arrangement

The 5BR8 is the same as the 6BR8 except for the following items:

Heater, for Unipotential Cathodes:

Voltage.	4.7	ac or dc volts
Current.	0.6	amp
Warm-up time (Average)*.	11	sec

* For definition of heater warm-up time and method of determining it, see sheet HEATER WARM-UP TIME MEASUREMENT at front of this Section.