

8JU8A

Quadruple Diode

The 8JU8A is the same as the 6JU8A except for the following items:

Heater Characteristics and Ratings

| | | |
|--|---------------|---|
| Current. | 0.450 ± 0.030 | A |
| Voltage (AC or DC) at 0.450 A. | 8.4 | V |
| Warm-up time (Average) | 11 | s |

8JV8

High-Mu Triode—Sharp-Cutoff Pentode

The 8JV8 is the same as the 6JV8 except for the following items:

Heater Characteristics and Ratings

| | | |
|---|---------------|---|
| Current. | 0.450 ± 0.030 | A |
| Voltage (AC or DC) at 0.450 A | 8.5 | V |
| Warm-up time (Average) | 11 | s |

8KA8

High-Mu Triode—Sharp-Cutoff Pentode

Pentode Unit Has Two Independent Control Grids

The 8KA8 is the same as the 6KA8 except for the following items:

Heater Characteristics and Ratings

| | | |
|---|---------------|---|
| Current. | 0.450 ± 0.030 | A |
| Voltage (AC or DC) at 0.450 A | 8.4 | V |
| Warm-up time (Average) | 11 | s |

8LC8

High-Mu Triode—Sharp-Cutoff Pentode

The 8LC8 is the same as the 6LC8 except for the following items:

Heater Characteristics and Ratings

| | | |
|---|---------------|---|
| Current. | 0.450 ± 0.030 | A |
| Voltage (AC or DC) at 0.450 A | 8.4 | V |
| Warm-up time (Average) | 11 | s |

