

6KM8

Diode— Sharp-Cutoff Three-Plate Tetrode

9-PIN MINIATURE TYPE

For Frequency-Divider and Complex-Wave-Generator Circuits of Electronic Musical Instruments

GENERAL DATA

Electrical:

Heater Characteristics and Ratings (*Design-Maximum Values*):

Voltage (AC or DC) 6.3 ± 0.6 volts

Current at heater volts = 6.3 0.300 amp

Peak heater-cathode voltage:

Heater negative with respect to cathode 200 max. volts

Heater positive with respect to cathode 200^a max. volts

Direct Interelectrode Capacitances:^b

Tetrode Unit:

Grid No.1 to plate 1A 0.02 max. pf

Grid No.1 to plate 1B 0.02 max. pf

Grid No.1 to plate 2 0.06 max. pf

Grid No.1 to cathode & internal shield, grid No.2, and heater 5.5 pf

Plate 1A to cathode & internal shield, grid No.2, and heater 1.2 pf

Plate 1B to cathode & internal shield, grid No.2, and heater 1.3 pf

Plate 2 to cathode & internal shield, grid No.2, and heater 1.8 pf

Tetrode grid No.1 to diode plate 0.024 max. pf

Tetrode plate 1A to diode plate 0.18 pf

Tetrode plate 1B to diode plate 0.024 pf

Tetrode plate 2 to diode plate 0.013 pf

Characteristics, Class A₁ Amplifier (Tetrode Unit):

Plates 1A, 1B, and 2 connected together at socket

Plate Voltage 100 volts

Grid-No.2 Voltage 100 volts

Grid-No.1 Supply Voltage 0 volts

Grid-No.1 Resistor (Bypassed) 2.2 megohms

Plate Resistance (Approx.) 30000 ohms

Transconductance 3400 μmhos

Plate Current 4.2 ma

Grid-No.2 Current 1.7 ma

Grid-No.1 Voltage (Approx.) for plate μ_a = 20 -4 volts

Triode Connection—

Grid No.2 connected to plates 1A, 1B, and 2 at socket

Plate Voltage 100 volts

Grid-No.1 Supply Voltage 0 volts



6KM8

Grid-No.1 Resistor (Bypassed)	2.2	megohms
Transconductance.	4500	μ hos
Amplification Factor.	45	
Plate Current	5.5	ma


Separate plate operation, plates not under test grounded

Plate Voltage:		
Plate 1A.	100	volts
Plate 1B.	100	volts
Plate 2	100	volts
Grid-No.2 Voltage	100	volts
Grid-No.1 Supply Voltage.	0	volts
Grid-No.1 Resistor (Bypassed)	2.2	megohms
Transconductance:		
Grid No.1 to plate 1A	2000	μ hos
Grid No.1 to plate 1B	2000	μ hos
Grid No.1 to plate 2.	1800	μ hos
Plate Resistance (Approx.):		
Plate 1A.	0.1	megohm
Plate 1B.	0.1	megohm
Plate 2	0.12	megohm
Plate Current:		
Plate 1A.	2.3	ma
Plate 1B.	2.3	ma
Plate 2	2.1	ma
Grid-No.2 Current:		
For plate 1A volts = 100.	3.8	ma
For plate 1B volts = 100.	3.8	ma
For plate 2 volts = 100	3.3	ma

Mechanical:

Operating Position.	Any
Type of Cathode	Coated Unipotential
Maximum Overall Length.	2-5/8"
Maximum Seated Length	2-3/8"
Length, Base Seat to Bulb Top (Excluding tip)	2" \pm 3/32"
Diameter.	0.750" to 0.875"
Dimensional Outline	See <i>General Section</i>
Bulb.	T6-1/2
Base.	Small-Button Noval 9-Pin (JEDEC No.E9-1)
Basing Designation for BOTTOM VIEW.	9QG

- Pin 1 -Tetrode
Plate 1B
- Pin 2 -Tetrode
Plate 1A
- Pin 3 -Diode
Plate
- Pin 4 -Heater
- Pin 5 -Heater



- Pin 6 -Cathode,
Internal
Shield
- Pin 7 -Tetrode
Grid No.1
- Pin 8 -Tetrode
Grid No.2
- Pin 9 -Tetrode
Plate 2



6KM8

FREQUENCY-DIVIDER & COMPLEX-WAVE-GENERATOR SERVICE

TETRODE UNIT

Maximum Ratings, Design-Maximum Values:

PLATE VOLTAGE:		
PLATE 1A.	330 max.	volts
PLATE 1B.	330 max.	volts
PLATE 2	330 max.	volts
GRID-No.2 (SCREEN-GRID)		
SUPPLY VOLTAGE.	330 max.	volts
GRID-No.2 VOLTAGESee <i>Grid-No.2 Input Rating Chart</i> at front of Receiving Tube Section	
GRID-No.1 (CONTROL-GRID) VOLTAGE:		
Negative-bias value	50 max.	volts
Positive-bias value	0 max.	volts
GRID-No.2 INPUT:		
For grid-No.2 voltages up to 165 volts	0.65 max.	watt
For grid-No.2 voltages between 165 and 330 voltsSee <i>Grid-No.2 Input Rating Chart</i> at front of Receiving Tube Section	
PLATE 1A DISSIPATION.	1 max.	watt
PLATE 1B DISSIPATION.	1 max.	watt
PLATE 2 DISSIPATION	1 max.	watt

Maximum Circuit Values:

Grid-No.1-Circuit Resistance:		
For grid-No.1-resistor- bias operation.	2.2 max.	megohms

DIODE UNIT

Maximum Ratings, Design-Maximum Values:

PLATE CURRENT	1 max.	ma
-------------------------	--------	----

Characteristics, Instantaneous Test Condition:


Plate Current for plate volts = 10. . .	2	ma
---	---	----

^a The dc component must not exceed 100 volts.
^b without external shield.



6KM8

AVERAGE CHARACTERISTICS Tetrode Unit




92CM-11713RI

RADIO CORPORATION OF AMERICA
Electron Tube Division
Harrison, N. J.



6KM8

AVERAGE PLATE CHARACTERISTICS Tetrode Unit—Triode Connection



92CM-11748



RADIO CORPORATION OF AMERICA
Electron Tube Division
Harrison, N. J.

DATA 3
1-63